

<b>CONTAINER CARRIER SEMI-TRAILER TECHNICAL SPECIFICATION</b>	
Tractor Type	— 4x2 tractor suitable for 1100mm King Pin Height. (Total GWA 44 tons)
Chassis	— High Graded Material “I” profile it is produced with gas welding, it has high-quality strength, Standard chassis Type. (Required changes will be made after the order confirmation) — Special reinforced bracket on the square beam profile at the front and rear. — Rear cross twist lock cross member will be 110 mm from the center to the edge of rear bumper. — Rear Bumper and light and license plate holder will be moved to the inner side with 100 mm. — Upper level of the chassis will not exceed 1150 mm with 385 65 R 22,5 tires.
Over All Length Dimension	— Length 9 700 mm x Width 2550 mm x Height 1250 mm — Wheelbase (between king pin and center of axles) +/- 7550 mm
Vehicle Type	— Skeleton chassis
Container twist lock	— 12 PCS. 1 x 20 feet, 2 x 20 feet, 1 x 30 feet, feet 1 x 40 feet and 1x 45 feet — 30 ft. cross member portable place is not needed to reinforce the neck of the chassis.
King Pin	— 2" kingpin and second king pin position. Jost or OMS brand — Pin detachable from below made by SAE standards 8 bolt type.
Axles	— 3 x 09.000 kg carrying capacity SAF brand Disc Brake Type — First axle with lifting mechanism, controlled manually on the chassis
Distance Between Axles	— 1320 mm
Brakes & Suspension	— Air Suspension — EBS Brake System KNORR brand, (2S/2M RSS) — Automatic Slack Adjuster — 3 units of 80 lt, 40 lt and one spare air tubes
Landing gear	— Double Speed, — 24000 kg carrying capacity SAF — Mechanical Landing Gears
Rear Bumper	— Suitable 70/221 / AT-version of the rear bumper
Tire Chock	— Carriers with 2-unit wheel chock
Tires and Rimes	— 6 PCS 385/ 65 R 22,5 Single tire type — Bridgestone brand — 120 offset 22,5 x 11,75 Rim, 280,8 x 335 x 10 wheel stud M 22 x 1,5
Mud Cover	— 6 Units full plastic mudguards fitted with galvanized steel holders.
Spear Wheel Carrier	— N/A or Optional
Toolbox	— N/A or Optional — Document holder
Water Tank	— N/A or Optional
Paint	— Steel Material surface is cleaned by grit metal and send, which is shot blasted on the surfaces of the metal. — 2 Floor Epoxy primers are made and final paint with standard RAL 7024 or demand of the customer, — Galvanization is optional.
Electrical System and Lightening System	— 3 unit's amber-colored lights placed on both sides — Park lamps at the rear side of the vehicle — License plate lamps, — Reflector triangles,

- Flameproof electrical system
- 2 X 7-pin and 1 x 15-pin electrical socket. (The connection pins will be mounted on special designed front panel)
- Electrical system is ASPÖCK brand Euro point 2 or Euro point 3

DRAWING



TELESKOBİK KONTEYNER TAŞIYICI

TELEKÖR YÜKLEMEYİ (mm)	ARAC ÖR. (mm)	TELESKOPİK MEREZİN ARALIĞI (mm)	BASİ MÖ. (mm)	YANIK TE. (mm)	DE. SET GÖRÜL. (mm)	DE. SET ÖL. (mm)
A	B	C	D	E	F	L
1150	1260	5500-7150	1300	2050	2550	8970-12200

